

1 Scheme

Questions

- 1.1 What will Scheme output? Draw the box and pointer whenever the expression evaluates to some pair or list.

```
> (or 'false (/ 1 0) 'true)
```

```
> '(1 2 3)
```

```
> (cons 2 '())
```

```
> (cons 1 (cons 2 '()))
```

```
> (cadar '((1 2) 3 (4 5)))
```

```
> (caddr '((1 2) 3 (4 5)))
```

```
> (cddar '((1 2) 3 (4 5)))
```

```
> (cddr '((1 2) 3 (4 5)))
```

- 1.2 Spot the bug(s). Test out the code and your fixes in the scheme interpreter! (<https://scheme.cs61a.org/>)

```
(define (sum-every-other lst)
  (cond ((null? lst) lst)
        (else (+ (cdr lst)
                  (sum-every-other (caar lst)) )))
```

- 1.3 Define **append**, which takes in two lists and concatenates them together.

```
> (append '(1 2 3) '(4 5 6))
(1 2 3 4 5 6)
```

2 Scheme, Exceptions

- 1.4 Define **reverse**. You may use **append** in your definition.

```
> (reverse '(1 2 3))
(3 2 1)
```

- 1.5 Define **reverse** without using **append**. (Hint: use a helper function and **cons**)

- 1.6 Define **add-to-all**, which takes in an item and a list of lists, and adds that item to the front of each nested list.

```
> (add-to-all 'foo '((1 2) (3 4) (5 6)))
((foo 1 2) (foo 3 4) (foo 5 6))
```

- 1.7 Define **map**, which takes in a function and a list, and applies that function to each item in the list.

```
> (map (lambda (x) (+ x 1)) '(1 2 3))
(2 3 4)
```

- 1.8 Define **add-to-all** using one call to **map**. (Hint: consider using a lambda expression!)

- 1.9 Define **sublists**. (Hint: use **add-to-all**)

```
> (sublists '(1 2 3))
(()) (3) (2) (2 3) (1) (1 3) (1 2) (1 2 3)
```

- 1.10 Define **sixty-ones**, a function that takes in a list and returns the number of times that 1 follows 6 in the list.

```
> (sixty-ones '(4 6 1 6 0 1))
1
> (sixty-ones '(1 6 1 4 6 1 6 0 1))
2
> (sixty-ones '(6 1 6 1 4 6 1 6 0 1))
3
```

1.11 Define **no-elevens**, a function that takes in a number *n*, and returns a list of all distinct length-*n* lists of 1s and 6s that do not contain two consecutive 1s.

```
> (no-elevens 2)
((6 6) (6 1) (1 6))
> (no-elevens 3)
((6 6 6) (6 6 1) (6 1 6) (1 6 6) (1 6 1))
> (no-elevens 4)
((6 6 6 6) (6 6 6 1) (6 6 1 6) (6 1 6 6) (6 1 6 1) (1 6 6 6) (1 6 6 1) (1 6 1 6))
```

2 Exceptions

Questions

2.1 How do we raise exceptions in Python?

2.2 How do we handle raised exceptions? And why would we need to do so?